

KANGOUROU	Spécification	Modèle K1	Modèle K1Remorque	Modèle K1S
Dimensions	Lenght	2991mm	4350mm	6630mm
	Widht	2438mm	2280mm	2280mm
	Height	2591mm	2360mm	2870mm
	Weight	2430kg	1740kg	1960kg
Operation storage and transportation	Operation	≥ 5°C ≥ 10RH	≥ 5°C ≥ 10RH	≥ 5°C ≥ 10RH
	Storage	0 to 75°C	0 to 75°C	0 to 75°C
Air filters	Filtration Method	G4 -G7		
Water product and purification	Ph	6,8-7,2	6,8-7,2	6,8-7,2
	Purification method	Filter and UV lamp		
	production capacity day*	1135 litres/day		
	Refrigerant	r454c		
	Dspensing options	ambient		
Accoustic	Noise level	74dba		
Lifting and transportation platform	Transportation	Standard cargo		
	Lifting	Forklift or crane		
Electricity	Nominal opération voltage	400 3 ph 50 Hz / 440 3ph 60 Hz		
	Allowed deviation phases	not applicable		
	Power consumption	8,4 kW	8,4kW	0
	Energy Efficiency *	50 Wh/litre		
	Circuit breaker current	40 A		
	Main power connection	4 x 10mm ²		
	Main power supply	not applicable		
Certifications	Electrical safety	CE CA CB IEC6024-41	CE CA CB IEC6024-41	CE CA CB IEC6024-41
	Water safety	IS-5452	IS-5452	IS-5452