

TIGGER	Spécification	Modèle T3	Modèle T5	Modèle T10
Dimensions	Lenght	6060mm	6060mm	6060mm x 2
	Widht	2380mm	3280mm	2380mm
	Height	2540mm	3540mm	3540mm
	Weight	4300kg	4700kg	8800kg(4400x2)
Operation storage and transportation	Operation	≥ 5°C ≥ 10RH	≥ 5°C ≥ 10RH	≥ 5°C ≥ 10RH
	Storage	0 to 75°C	0 to 75°C	0 to 75°C
Air filters	Filtration Method	G4 -G7		
Water product and purification	Ph	6,8-7,2	6,8-7,2	6,8-7,2
	Purification method	Filter and UV lamp		
	production capacity day*	3500 litres/day	5200 litres /day	10400 litres /day
	Refrigerant	r454c		
	Dsipensing options	ambient		
Accoustic	Noise level	74dba		
Lifting and transportation platform	Transportation	Standard cargo		
	Lifting	Forklift or crane		
Electricity	Nominal opération voltage	not applicable		
	Allowed deviation phases	not applicable		
	Power consumption	SOLAR		
	Energy Efficiency *	50 Wh/litre		
	Circuit breaker current	not applicable		
	Main power connection	not applicable		
	Main power supply	not applicable		
Certifications	Electrical safety	CE CA CB IEC6024-41	CE CA CB IEC6024-41	CE CA CB IEC6024-41
	Water safety	IS-5452	IS-5452	IS-5452